



PRODUCT DESCRIPTION

KULR's SafeSLEEVE is a DOT permitted Passive Propagation Resistant (PPR) storage and transportation system for batteries. It is designed to mitigate thermal runaway, providing safe and sustainable storage and transportation for lithium-ion cells and battery packs that are up to 0.3 kWh per sleeve and utilizes KULR's patented ³Thermal Runaway Shield® (TRS) technology. It can be customized upon request.

FEATURES AND BENEFITS

- DOT approved for ground transportation
- Rated Up to 0.3 kWh per sleeve
- Reusable
- Sustainable
- Safe nontoxic construction

TYPICAL APPLICATIONS

SafeSLEEVE can be customized to fit any application within the rated energy limit but is typically used for lithium-ion cell/battery storage, transportation, and DDR/hazardous li-ion battery recovery and recycling.

TYPICAL PROPERTIES

PROPERTY	TYPICAL VALUE	TEST METHOD
External Case		
Color	Black	Visual
Maximum Operating Temperature	900+°C	Material Prop
TRS		
Construction	Encapsulated Coolant	N/A
Maximum Energy Rating	300 Wh	DOT Approved TR Test ²
¹ Product Assembly Thickness	2 mm	Micrometer
¹ Tensile Strength (at break)	>14 lbs	ASTM D882
¹ Tear Strength (375F;26psi; 1 sec)	>1.7lbs	ASTM689
Seal Strength (375F;26psi; 1 sec)	12 lbs/in	ASTM D882
¹ Puncture Strength	>25 lbs	TMS 101-C, Method A

¹For further information see TRS Technical Data Sheet,

²DOT test performed by KULR to receive permits #21139,21167,21193,21693,21704

³U.S. Patent No. US-11018397-B, US-11502352-B2, US-10727462-B2



PROPERTY	TYPICAL VALUE	TEST METHOD
Ablative Reinforcement		
Tensile Strength	>80MPa	ASTM D638
Compression Strength	>180MPa	ASTM D695
Flexural Strength	>80MPa	ASTM D790

PRODUCT	DIMENSIONS	RATING	EMPTY WEIGHT	MAXIMUM WEIGHT	ABLATIVE REINFORCEMENT
SafeSLEEVE (K-SXS-000001)	13"W x 16.0"D	0.3 kWh	3.8lbs	10lbs	Yes

AVAILABILITY

SafeSLEEVE can be engineered in custom sizes. Please contact KULR Technology Group for additional information.

DISCLAIMER

Data on this Technical Data Sheet (TDS) are typical values and for reference only. The information provided in this TDS, including but not limited to the recommendations for use and application of the product, are based on our knowledge and experience of the product. The product can have a variety of different applications, as well as differing working conditions and environments that are beyond our control. Factors or events that could cause actual results to differ may emerge from time to time, and it is not possible for us to predict all of them. We cannot guarantee future results, performance, or achievements. Furthermore, no representations or warranties are made as to the accuracy or reasonableness of any assumptions on which the data or information is based.

This product is not intended for use with any products containing lithium metal. KULR Technology Group, Inc. is, therefore, not responsible, or liable for the suitability of our products for the production processes and conditions in respect of which you use them, as well as the intended applications and results. We strongly recommend that you conduct your own prior trials to confirm such suitability of our product for your use and application and within your working conditions and environments.